

# EC-DECLARATION OF CONFORMITY



**Manufacturer:** FRIEDRICH Schwingtechnik GmbH, Am Höfgen 24, D - 42781 Haan  
**Distributor:** FRIEDRICH Schwingtechnik GmbH, Am Höfgen 24, D - 42781 Haan



We herewith declare that the:

**VIMARC – vibrator motor series YE ...-... , und HXE(Z) – KXE(Z)**

in its design and type as well as by us sold execution is in conformity with the following European Directive:

1. 94/9/EC - DIRECTIVE 94/9/EC OF THE EUROPEAN PARLIAMENT AND THE COUNCIL OF 23 MARCH 1994 ON THE APPROXIMATION OF THE LAWS OF THE MEMBER STATES CONCERNING EQUIPMENT AND PROTECTIVE SYSTEMS INTENDED FOR USE IN POTENTIALLY EXPLOSIVE ATMOSPHERES

The following harmonized standards have been used::

-IEC 60079-0	<i>Electrical apparatus for explosive gas atmospheres- General requirements</i>
-IEC 60079-7	<i>Electrical apparatus for explosive gas atmospheres- Increased safety „e“</i>
-DIN EN 61241-1	<i>Electric machinery for use in surroundings with burnable dust part 1:</i>
	<i>Electric machinery with protection by housing</i>
-DIN EN 60034-5	<i>Rotating machinery part 5: classification of protection by housing of rotating machinery</i>

The named product is intended for fitting in another machine. Commissioning is prohibited until such time as the end product has been proved to conform to the provisions of Directive 2006/42/EC.

Frequency converter operation: the above designated motors for areas with combustible dust  
**Group II, Category 3GD (Zone 22) Temperature class 120°**  
**are allowed exclusively together with a Frequency converter of the manufacturer**  
**Loher Type line Dynavert T**

and can be pursued in accordance with the installation regulations DIN EN 60079-14 (VDE 0165-1) :2009-05:

- in a frequency response of 25Hz to maximum frequency up to the type plate given maximum frequency
- if built-in PTC thermistor are used in connection with a tipping device certified by a named Authority
- the voltage peaks arising in the system converter-cable-electrical machinery do not exceed twice the value of the link voltage (<2kV)

The nominal data and other data given on the type plate are related to the nominal operation (no converter feeding) and are only reference purposes for the converter feeding.

The used thermal winding protection is designated on the type plate.

The DECLARATION OF CONFORMITY expires by misapplication as well as by engineering change which was not confirmed by us as the manufacturer in writing.

The safety instructions provided in the product manual must be observed.

This Declaration does not give assurance of properties within the meaning of product liability.